

## 55 NORMAL HEADROOM HOIST NC, REEVING: 04, CURVED TRACK

### Hoist dimensions

HOL m	Length code	M1 mm	M2 mm	H1 mm	H2 mm	H3 mm	H3* mm	Weight kg
6	B	356	165	205	49	555	571	360
9	C	456	165	205	73	555	571	400
12	D	556	193	430	97	555	571	550
15	E	676	193	430	121	555	571	565

### Motor dimensions

Motor	P3	P4	A3	S3	S5
MOT (mm)	473	574	443	523	602
Weight (kg)	35	53	32	28	53

### Travelling dimensions

Motor	MF06LA
TMO (mm)	400
Weight (kg)	7.8

### Trolley dimensions

B1 min	B1 max	B2 min	B2 max	C1	C2	ØBU	ØWD	BU	BUH	GEA	H4
80	450	90	350	870	1030	63	100	253	40	116	638
TH	TS	TW									
150	523	31									

### Trolley dimensions

Length code	BUF	E1	E2	TD	TF
B/C	522	313	425	586	40
D/E	967	357	381	746	42

D003841\_A  
062169

### Track radius

B	R min
80 - 109	2500
110 - 119	2000
120 - 450	1500

Note: All dimensions in mm.

Note: Weight calculated with P3 motor.

Note: Motor S5 is unavailable for load class 6300 kg.

\* Please, disregard the dimension H3\*.

Normal Headroom Hoist NC, REEVING: 04, Curved Track

